

PERFORMANCE PLUS™ "F" & BNC Cables

ARIA Technologies, Inc. has designed its PERFORMANCE PLUS™ brand to accommodate the need for high quality, consumer based 75Ω coaxial video cables. These cables primarily consist of RCA, BNC and "F" connectors and are engineered and designed for TV/VCR/DVD and related equipment.

CATV Quad-Shielded Single Video Assemblies

Assembled 75Ω RG6 video cable with snap & seal type "F" connectors.
Commonly used for TV to VCR/DVD and Satellite/Cable Boxes.

FA6QFMMzzH Male to Male, custom length
Replace "zz" with custom length.



RG-6 Digital Video BNC Cables

Available in (BU) Blue, (WT) White, (GN) Green, (RD) Red.

PBNCR6MMzzX Assembled Male to Male, custom length
PMBNCR6MMzzX Molded Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



CATV Single Video Assemblies

Assembled 75Ω video cable with threaded "F" connectors.
Commonly used for TV to VCR/DVD and Satellite/Cable Boxes.

PA75FMMzzX Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



RG-59 Digital Video BNC Cables


PBNCR59MMzzX Assembled Male to Male, custom length
PMBNCR59MMzzX Molded Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



CATV Single Video Outdoor Assemblies

Assembled 75Ω video cable with "F" connector.
Commonly used for outside cable hook up or satellite dish to VCR, cable or satellite box and/or output device to TV display.

PAF59MMzzX RG59 Male to Male, custom length
PAF6MMzzX RG6 Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



BNC Single Video

75Ω coaxial video cable.
Commonly used for single video security and Video Display Applications.

PBNCR75MMzzX Assembled Male to Male, custom length
PMBNCR75MMzzX Molded Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



RG6 Molded "F" Cables

Molded "F" connectors with strain relief.

PMF6MM03 Male to Male, 3ft.
PMF6MM06 Male to Male, 6ft.
PMF6MM12 Male to Male, 12ft.
PMF6MM25 Male to Male, 25ft.
PMF6MM50 Male to Male, 50ft.
PMF6MM100 Male to Male, 100ft.



RG-59 Mini Digital Video BNC Cables

PBNCR59MMzzX Assembled Male to Male, custom length
PMBNCR59MMzzX Molded Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



RG59 Molded "F" Cables

Molded "F" connectors with strain relief.

PMF59MM03 Male to Male, 3ft.
PMF59MM06 Male to Male, 6ft.
PMF59MM12 Male to Male, 12ft.
PMF59MM25 Male to Male, 25ft.
PMF59MM50 Male to Male, 50ft.
PMF59MM100 Male to Male, 100ft.



RCA/BNC Signal Video

75Ω coaxial video cable.

PRCABNC175MMzzX Assembled Male to Male, custom length
PMRCABNC175MMzzX Molded Male to Male, custom length
Replace "zz" with custom length.
Replace "X" with "F" for Feet or "M" for Meters.



Coaxial Custom Ordering Chart



Custom Coaxial Cable Numbering System

Use the chart below to generate a part number to match your exact needs.



Typical Part Number → **P P 213 AF 98 MF 150 F**

Material
P = PVC
T = Plenum

UNIT OF MEASURE
I = Inch
F = Feet
M = Meters

CABLE TYPES

6 = RG-6	300 = LMR300
8 = RG-8	303 = RG-303
11 = RG-11	316 = RG-316
58 = RG-58	393 = RG-393
59 = RG-59	40G = RG-400
62 = RG-62	195 = LMR195
100 = LMR-100	240 = LMR240
141 = RG-141	400 = LMR400
161 = RG-161	500 = LMR500
174 = RG-174	600 = LMR600
178 = RG-178	402 = RG-402
179 = RG-179	405 = RG-405
188 = RG-188	734 = 734A
200 = LMR200	735 = RG-735
213 = RG-213	900 = LMR900
214 = RG-214	1200 = LMR1200
223 = RG-223	1700 = LMR1700

CONNECTOR TYPES (A & B)

A = BNC	O = SHV
B = TNC	P = Banana
C = N	Q = Double Banana
D = UHF	R = RCA
E = MINI UHF	S = 1/4" Mono
F = F Twist-On	T = 3.5mm Mono
G = F Push-On	U = 2.5mm Mono
H = Mini-Coax	V = Bantam Mono
I = SMA	W = Alligator Clips
J = SMB	(reverse polarity)
K = SMC	1 = BNC
L = MCX	2 = TNC
M = MMCX	3 = N
N = Mini-SMB	4 = SMA
	5 = MMCX

CONNECTOR ANGLE (A & B)

9 = 90°
8 = 180°

CONNECTOR GENDER (A & B)

M = Male
F = Female
B = Female Bulkhead
P = Male Bulkhead

Assembled cables will include heat shrink as a strain relief between connector body and cable, unless specified. Slide-on boots and mold injection is also available on some connector types, consult your sales representative at **(925) 447-7500**

