

PERFORMANCE PLUS™ S-Video Cables

Our molded, super-flexible S-Video assemblies made with dual low-loss 75Ω coax are the preferred choice among many in the professional video industry. Their low attenuation & capacitance specs allow for longer runs with less loss than a typical S-Video cable. Compact design, extremely high flexibility and low profile 4 pin Mini-Din connectors allow for use in high density environments. Custom lengths are readily available.

PERFORMANCE PLUS™ S-Video Cables, Assembled

(Application: Connects VHS/satellite or other video output device to TV)

PA75M4MMzzX S-Video Cable 75Ω, Male to Male, custom length
PA75M4MFzzX S-Video Cable 75Ω, Male to Female, custom length
 Replace "zz" with custom length and "X" with "F" for Feet or "M" for Meters.



PERFORMANCE PLUS™ S-Video Cables, Molded

(Application: Connects VHS/satellite or other video output device to TV)

PM75M4MM03 S-Video Cable 75Ω, Male to Male, 3ft.
PM75M4MM06 S-Video Cable 75Ω, Male to Male, 6ft.
PM75M4MM12 S-Video Cable 75Ω, Male to Male, 12ft.
PM75M4MM25 S-Video Cable 75Ω, Male to Male, 25ft.
PM75M4MM50 S-Video Cable 75Ω, Male to Male, 50ft.
PM75M4MM100 S-Video Cable 75Ω, Male to Male, 100ft.
CM75M4MMzzX S-Video Cable 75Ω, Male to Male, custom length
CM75M4MFzzX S-Video Cable 75Ω, Male to Female, custom length
 Replace "zz" with custom length and "X" with "F" for Feet or "M" for Meters.



PERFORMANCE PLUS™ S-Video Cables 90° Angle, Assembled

(Application: Connects VHS/satellite or other video output device to TV)

PM75M499MMzzX S-Video Cable 75Ω, 90° Male to 90° Male, custom length
PM75M498MFzzX S-Video Cable 75Ω, 90° Male to 180° Female, custom length
 Replace "zz" with custom length and "X" with "F" for Feet or "M" for Meters.



PERFORMANCE PLUS™ Plenum S-Video Cables, Assembled

Our plenum rated S-Video assemblies are designed for use in plenum airspace, eliminating the need for conduit. Each cable is handcrafted and 100% tested by ARIA Technologies, Inc. and utilizes our plenum cable to provide the best possible transmission of S-Video signals over long runs. The assemblies are available in custom lengths. Full rolls of bulk cable are sold in 1000ft. put-ups.

Cable Construction

Conductors:	2 x 25 AWG Solid	Diameter:	0.15 x 0.26 (oval)
Shield:	95% Spiral Wrapped	Capacitance:	16.2 pF/ft.
Dielectric:	FEP		

S-Video (Male) to S-Video (Male or Female)

PA75M4MMzzXP S-Video Cable 75Ω Plenum, Male to Male, custom length
PA75M4MFzzXP S-Video Cable 75Ω Plenum, Male to Female, custom length
PA75M499MMzzXP S-Video Cable 75Ω Plenum, 90° Male to 90° Male, custom length

Replace "zz" with custom length and "X" with "F" for Feet or "M" for Meters.



PERFORMANCE PLUS™ S-Video Cables & Adapters

PERFORMANCE PLUS™ S-Video + Audio Composite Assemblies

(Application: Connects VHS/satellite or other audio/video output device to TV)

PRCA224M4MMzzX S-Video + Left & Right Audio, Male to Male, custom length
 Replace "zz" with custom length and "X" with "F" for Feet or "M" for Meters.



S-Video Adapters & Dubbing Assemblies

These professional adapters and dubbing assemblies use low-loss, dual 75Ω coax designed and built by ARIA Technologies, Inc. They are extremely flexible and maintain the highest integrity S-Video signal. Custom configurations and lengths are readily available and are normally shipped within 7-10 business days. Call us for a quote.

S-Video Male to Dual BNC Female

PMD4M2BNCF18I 18"
PMD4M2BNCFzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



S-Video Male to Dual BNC Male

PMD4M2BNCMzzX custom length
 Replace "zz" with custom length.
 Replace "X" with I for Inches, F for Feet or "M" for Meters.



S-Video Male to Dual RCA Male

PMD4M2RCAMzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



S-Video Male to Dual RCA Female

PMD4M2RCAFzzX custom length
 Replace "zz" with custom length.
 Replace "X" with I for Inches, F for Feet or "M" for Meters.



S-Video Female to BNC Female

PMD4FBNCFzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



S-Video Female to RCA Female

PMD4FRCAF S-Video Female to RCA Female



S-Video Female to RCA Male

PMD4FRCAMzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



S-Video Male to RCA Female

PMD4MRCAF S-Video Male to RCA Female



S-Video Male to RCA Female

PMD4MRCAFzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



S-Video Female to S-Video Female

PMD4FF S-Video Female to S-Video Female



S-Video Male to RCA Male

PMD4MRCAMzzX custom length
 Replace "zz" with custom length.
 Replace "X" with "I" for Inches, "F" for Feet or "M" for Meters.



Custom Requirement?

High performance audio and video cables are available both off the shelf and in any custom configuration. Specify your custom S-Video cable need whether its plenum cable, special wiring configuration or multiple connector breakouts.