

FX IP67 Rated Cable Assemblies

FX IP67 Rated Cable Assemblies are weatherproof cable assemblies designed for remote radio units.

These assemblies provide robust Fiber to the Antenna (FTTA) connectivity.

FX assemblies are rodent resistant and feature bayonet locking style LC connectors for FTFA applications.

FX connector housings are removable and can be installed at any time to weatherproof any compatible assembly.

Available in 5mm or 7mm cable jacket sizes.



FullAXS IP67 Rated Cable Assemblies

- Meets IP67 Standards
- No tools required
- Bayonet style locking mechanism
- Designed for harsh environment applications
- 5mm and 7mm jacket sizes available
- Rodent resistant



Part Number



<div style="background-color: #00AEEF; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">1</div> <p>Cable Size</p> <p>5 = 5.0 mm 7 = 7.0 mm</p>	<div style="background-color: #E91E63; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">2</div> <p>Connector Type End 1</p> <p>FLCU = FULLAXS LC/UPC FSCU = FULLAXS SC/UPC FMPO = FULLAXS MPO</p>	<div style="background-color: #FFD700; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">3</div> <p>Connector Type End 2</p> <p>FLCU = FULLAXS LC/UPC RLCU = LC/UPC FSCU = FULLAXS SC/UPC RSCU = SC/UPC FMPO = FULLAXS MPO RMPO = MPO</p>	<div style="background-color: #D32F2F; color: white; padding: 5px; text-align: center; font-weight: bold; font-size: 24px;">4</div> <p>Length</p> <p>XXXXF = Length in Feet XXXM = Length in Meters</p>
---	--	---	--