

### XWM-4X Wallmount Enclosure



#### Overview

ARIA's XWM-4X is a compact wall mount fiber optic distribution enclosure designed to support patching and/or splicing.

The unit has the capacity to accept 4 LGX-type adapter plates allowing for the termination of a variety of connector types and fiber counts of up to 48 SC or 96 LC.

The unit has a key-lockable drop-down-door splice compartment which serves as a work shelf for splicing.

The patch side door comes equipped with a padlock hasp for additional security.

#### Specifications

Parameter	Value
<b>Dimensions (H"xW"xD")</b>	11.4 x 14.2 x 4.2
<b>Weight</b>	10 lbs
<b>Fiber Capacity</b>	48 fibers SC or 96 fibers LC
<b>Cable Entry</b>	Four 1.175" Openings
<b>Material</b>	16 Gauge Steel
<b>Finish</b>	Black electrostatically applied powder coat

#### Accessories



Grounding and Bonding Kit  
P/N: AWMGB-KIT



Medium Compression Fitting Supports Cable O.D.: 0.15"-0.70" (P/N: CF-MD)

### XWM-4X Wallmount Enclosure

#### Part Number



**1** Adapter Plate Type

06 = 6 Port (SC/FC/ST)  
 08 = 8 Port (SC/FC/ST)  
 12 = 12 Port (SC/LC)  
 24 = 24 Port (LC)

**2** Adapter Plate Quantity

1 = 1 Plate  
 2 = 2 Plates  
 3 = 3 Plates  
 4 = 4 Plates

**3** Adapter Type

Singlemode  
 SCU = SC/UPC  
 SCA = SC/APC  
 LCU = LC/UPC  
 LCA = LC/APC  
 FCU = FC/UPC  
 FCA = FC/APC  
 STU = ST/UPC

Multimode  
 SCM = SC  
 LCM = LC  
 FCM = FC  
 STM = ST

**4** Pigtail

N = No Pigtail  
 M = 900 µm in Mesh  
 R = Ribbon  
 D = Distribution Style (MIC)

Note: 3 meter pigtail length is standard

**5** Fiber Type

Singlemode  
 S = SMF-28e+  
 B = SMF Bend Insensitive G.657.A1

Multimode  
 1 = 62.5/125µm  
 2 = 50/125µm  
 3 = 50/125µm OM3  
 4 = 50/125µm OM4

**6** Splice Trays

N = None  
 Y = Yes\*

\*This enclosure comes standard with 4.0"x8.0" splice trays in 24 fiber single fiber or 6 position ribbon fiber configurations.

**7** Stub Cable Type

Leave Blank for No Stub

DR = Distribution Style Riser Rated  
 DP = Distribution Style Plenum Rated  
 AP = Interlocking Armor Plenum Rated  
 IR = Indoor/Outdoor Riser Rated  
 IP = Indoor/Outdoor Plenum Rated  
 OA = Outside Plant Armored  
 ON = Outside Plant Non-Armored  
 AJ = Non-Armored Alternative Jacket

**8** Stub Length

Leave Blank for No Stub

XXXF = XXX Feet  
 XXXM = XXX Meters