

XWM-4X

Wallmount Enclosures



Overview

The XWM-4X is a compact wall mount fiber optic distribution enclosure designed to support patching and/or splicing.

The unit has the capacity to accept 4 LGX-type adapter plates allowing for the termination of a variety of connector types and fiber counts of up to 48 SC or 96 LC.

The unit has a key-lockable drop-down-door splice compartment which serves as a work shelf for splicing.

The patch side door comes equipped with a padlock hasp for additional security.

Specifications

Dimensions (Inches)	11.4 x 11.2 x 4.2 (HxWxD)
Adapter Plate Capacity	4
Fiber Capacity	48 SC or 96 LC
Cable Entry Openings	Patch Side: (2) 1.175" Splice Side: (2) 1.175"
Material	1.5mm Thick Steel
Material Finish	Black Powdercoat
Weight (Empty) (lbs)	10.0

Accessories



Grounding and Bonding Kit
P/N: AWMGB-KIT



Medium Compression Fitting Supports Cable O.D.: 0.25"-0.49"
P/N: CF-MD



Three Slot Flat Drop Compression Fitting with Removable Spacers
P/N: CF-3S-FD

Part Number



1 Adapter Plate Type
06 = 6 Port (SC/FC/ST)
08 = 8 Port (SC/FC/ST)
12 = 12 Port (SC/LC/FC/ST)
24 = 24 Port (LC)

2 Adapter Plate Quantity
1 = 1 Plate
2 = 2 Plates
3 = 3 Plates
4 = 4 Plates

3 Adapter Type
Singlemode
SCU = SC/UPC
SCA = SC/APC
LCU = LC/UPC
LCA = LC/APC
FCU = FC/UPC
FCA = FC/APC
STU = ST/UPC

Multimode
SCM = SC
LCM = LC
FCM = FC
STM = ST

4 Pigtail
N = No Pigtail or Pre-Term
M = 900 µm in Mesh
D = Distribution Style (MIC)
R = Ribbon in Mesh

Note: 3 meter pigtail length is standard

5 Fiber Type
Singlemode
S = SMF-28e+
B = SMF Bend Insensitive G.657.A1

Multimode
1 = 62.5/125µm OM1
2 = 50/125µm OM2
3 = 50/125µm OM3
4 = 50/125µm OM4

6 Splice Trays
N = None
Y = Yes*

*This enclosure comes standard with 4"x8" splice trays in 24 fiber single fiber fusion or 6 position ribbon fiber mass fusion configurations.

7 Stub Cable Type
Leave Blank for No Stub

Indoor
IR = Riser Rated
IP = Plenum Rated
IA = Interlocking Armor Plenum Rated

Indoor/Outdoor
XR = Riser Rated
XP = Plenum Rated
XC = Central Tube Riser Rated

Outdoor
ON = Non-Armored
OA = Armored Central Tube
OL = Armored Loose Tube
AJ = Non-Armored Alternative Jacket
OR = Ribbon Armored Central Tube
FD = Flat Drop

8 Stub Length
Leave Blank for No Stub
Add -PE for a Pulling Eye

XXXF = XXX Feet
XXXM = XXX Meters